

RIVEER RIPTIDE™ PRESSURE WASHER

Need a faster solution to washing down your oily frac tanks? Hard to clean drilling rigs delaying your teardown? Standby, here comes the Riveer™ RipTide™ Pressure Washer. Say adios to grimy tanks, fittings, hardware and hard to reach girders and field rigs; say hello to cleaner equipment. Designed to tackle tough cleaning jobs faster, more efficiently, Riveer RipTide features full-bore water delivery technology, giving you diesel-powered washing performance up to 3,000 PSI.

RipTide pumps out 16 to 90 GPM depending on configuration. This self-contained unit is available with one, two or three pumps; each operating independently in water pressure, temperature and if needed, solvent mix. You can blast, foam and rinse. Hot water, warm water, cold water. All on the same machine. Operating on diesel from an 18-gallon fuel tank (larger available), RipTide requires no external power, ideal for field operations without utilities.

Accessories include spray wands, foaming guns and water cannons, and because we make RipTide, we can build one to your specs.



RipTide™ Pressure Washer

Skid mounted RipTide™ is built rock solid, in a urethane painted steel frame suitable for forklift or crane. Open access design makes oil change and routine maintenance quick and easy on this hot water pressure washer that is specially designed to make maintenance simple and worry free.

PRESSURE WASHER SPECIFICATIONS:

- 24 HP – 35 HP Kubota® diesel engine
- 12 – 35 gallon fuel tank for engine
- 12 – 35 gallon fuel tank for burners
- Individual CAT pressure pumps for true 4.5 GPM @ 3000 PSI operation
- Belt driven clutch for improved control and performance
- Controls allow individual 1, 2 or 3 pump on/off as required for fuel savings and less wear on plumbing components
- Each pump directly feeds a hose reel
- Each user has a Reelcraft hose reel with 100ft of hose
- Engine is equipped with speed control to save wear on machine and fuel
- GripStart™ controls throttle; idle when trigger is released and throttles up when trigger is squeezed
- Low float protection prevents machine from being run dry and damaging pumps
- **Capacity:** 16 to 90 GPM
- **Weight:** 2250 lbs
- **Dimensions:** 9' L x 4' W x 58" H



WATER CANNON ADD ON

- 14.5 HP Kubota Diesel Engine
- 12 Gallon Fuel Tank
- Direct Driven HYPRO Pump
- 21 GPM @ 500 PSI
- Adjustable spray wand allows user to change from stream to fog

HOT WATER CONFIGURATION

- Each heater provides 120°F temp rise
- Made in USA Wayne Combustion burner
- Additional 12 – 35 gallon fuel tank provides approximately 12hrs run time without needing refueling
- Adjustable temperature control

GripStart™



RipTide is available with your choice of water cannons, foamers and spray wands.



Riveer employs a quality management system that is ISO 9001:2008 certified.
©2013 RIVEER. All rights reserved. Specifications subject to change. R1.13

RIVEER | 233 VETERANS BLVD | SOUTH HAVEN MI | RIVEER.com | 888.857.7304

RIVEER™
**Engineered Wash Water
Recovery Systems**